Heating Cable

Mt. Airy, MD

EL Standard

Connection Accessories

- · Junction Box Connection Kits for SRL, SRF and CWM **Applications**
- · Splice & Tee Kits for SRL, SRF and CWM Applications
- **End Seal Kits for SRL and SRF Applications**



Description

Each model in the EL Series Installation Accessories for Chromalox Rapid Trace Heating Cable products is designed to satisfy the demands of a particular operation. These highquality models combine a variety of functions in a convenient, easy to use and economical package.

Applications

Connection of selected rapid trace heating cables to customer supplied power wiring in any of the following applications:

- · Freeze Protection
- · Hydrocarbon and Chemical Product Piping
- Process Temperature Maintenance
- · Fluid Flow and Viscosity Maintenance.

Approvals

UL* Listed for ordinary areas

CSA* Certified for ordinary areas

 $\textbf{FM**} \ \, \textbf{Approved for ordinary areas}$

- * Does not include SSK
- ** Does not include SSK and PJB

Ordering Information

	Model	Used With	
Power Connection Kit		nection Kit	
	SSK PJB	SRF-C, SRF-CR, SRL-C, SRL-CR, SRL-CT, CWM-C, CWM-CT, SRP-C, SRP-CT	
	Splice & Tee Kit		
	RT-RST RT-TST	SRL-C, SRL-CR, SRF-C CWM-C, CT, SRP-C, SRP-CT	
	End Seal Kit		
٠	RT-RES	SRL-C, SRL-CR, SRF-C	
	To Order — Refer to the DL & EL General Application Accessories in this section.		

Heating Cable

EL

Standard Connection Accessories (cont'd.)

Accessories



Junction Box Connection Kit SSK (393617)

- (1) compression fitting
- (1) pipe stand off
- (1) tube of RTV sealant
- (1) O-ring
- (1) 1" locknut
- (1) self-regulating cable grommet
- (1) constant wattage cable grommet
- (1) silicone boot
- (2) uninsulated barrel connectors
- (2) insulated barrel connectors



Caution Labels CL-1 (382424)

(5) electric heat tracing caution labels. weather resistant



Rain Tight Junction Box PJB (393676)

Polycarbonate watertight enclosure for use with SSK



Splice & Tee Kit (for Constant Wattage and SRM/E Cable) RT-TST (383566)

- (5) 7" long large heat shrink tubes (10) 1-1/2" long small heat shrink
- (5) 10" lengths of sealant tape
- (15) uninsulated barrel connectors
- (1) tube of RTV sealant



End Seal Kit (for SRL cable) RT-RES (383574)

(5) 1/2" diameter heat shrink caps



Splice & Tee Kit (for SRL cable) RT-RST (383558)

- (5) 8" long heat shrink tubes
- (5) 1/2" lengths of sealant tape
- (10) insulated barrel connectors (5) uninsulated barrel connectors



Conduit Hub w/Grounding Lug CCH-2 (385650)

Corrision resistant hub for 3/4" conduit. Fits opening in PJB, DL, U Series and DTS. Includes ground connector.